

TASKI® swingo 1260 B

Battery-powered automatic scrubber drier



Key Features

- ▶ Ideal size for best performance
- ▶ Excellent cleaning and drying results
- ▶ Simplicity and easy maintenance
- ▶ Durability and robustness

Ideal size for best performance

The machine's patented IntelliFlow system always ensures the right amount of cleaning solution on the floor and leads to significant water savings up to 50%. This feature, in combination with the 60 litre tank volume, increases productivity and reduces time-consuming tank filling stops during the cleaning operation. The dual-axle system ensures easy handling and allows comfortable use of the machine.

Excellent cleaning and drying results

The machine's patented brush design follows the floor profile and delivers nearly even pressure allocation along the full working width. Two brushes are offset to the side, allowing superior cleaning along walls and under racks. This results in excellent soil removal and floor appearance. The patented V-shaped squeegee allows excellent water pick-up on all floor types, even on structured and grouted/tiled floors. Special squeegee blades and a direct suction line allow pick-up of small debris (e.g. cigarette butts) without clogging. Due to the proven three wheel concept, adjustments of the squeegee are no longer necessary.

Simple to use and easy maintenance

All components needing frequent maintenance are color-coded in yellow and can be removed easily without tools. The dashboard is self-explanatory and displays all required information. Fewer parts to maintain and easy accessibility make the machine extremely service friendly and offer significant time savings.

Durability and robustness

The use of high-tech material and long life components enhance the machine's uptime, while reducing service and repair costs to a minimum.

TASKI swingo 1260 B Specifications

Technical Data

Description		Description	
Theoretical performance	2475 m ² /h	Dimensions (L x W x H)	142 x 58 x 117 cm
Working width	55 cm	Turning circle	1.33 m
Squeegee width	80 cm	Brush system	2 x 28 cm
Solution tank (nominal)	60 l	Brush pressure	48 kg
Recovery tank (nominal)	60 l	Cleaning speed	4.5 km/h
Nominal consumption	1,000 W	Sound level	58 dB(A)
Rated voltage	24 V	Protection class	III
Battery capacity	100-140 Ah/C5	Approvals	CE/CB Test cert.
Battery run time (nominal)	up to 3 h		
Machine weight ready for use	260 kg		

TASKI swingo 1260 B

Model	SKU Number
TASKI swingo 1260 B Power	7518541

Accessories/Additional Parts

Description	SKU Number
Pad drive harpoon grip 28 cm (2 required)	7510634
Scrubbing brush standard 28cm (2 required)	7510631
Scrubbing brush washed concrete 28cm (2 required)	7510632
Scrubbing brush abrasive 28 cm (2 required)	7510633
Filling hose with universal water coupling (2 required)	8502830
Variety of polyester and contact pads Please refer to local price list	

Additional Features

IntelliFlow (Cleaning Solution Dosing): The IntelliFlow system allows for a speed-dependent supply of cleaning solution. This feature ensures that the amount of solution dosed onto the floor is always constant—no matter how fast the machine is operating. The result? No puddles in curves and turns as well as a 30-50 % saving in cleaning solution, leading to significantly increased productivity of the machine.

WD (Wheel Drive): The variable working speed up to 4.5 km/h and reverse speed up to 3 km/h guarantees ergonomic and effortless utilization and increases performance compared to non-wheel drive models.