

# TASKI® swingo® 755 B

## Battery-powered automatic scrubber drier



---

### Key Features

- ▶ Agility and high performance
- ▶ Excellent cleaning and drying result
- ▶ Durability and robustness
- ▶ Simplicity and easy maintenance

### Perfect combines agility, high performance

- ▶ The swingo 755 B is very easy to handle and offers maximum agility for use in confined areas. The dual-axle system allows for turning the machine literally on the spot, which leads to excellent manoeuvrability in tightly congested areas. The 40 litre tank volume reduces the time-consuming tank filling stops during the cleaning operation.

### Excellent cleaning and drying results

- ▶ The machine's patented brush follows the floor profile and delivers nearly even pressure allocation along the full working width, which leads to excellent soil removal. The new, patented V-shaped squeegee enables excellent water pick-up on the floor. Due to the proven three wheel concept, adjustments of the squeegee are no longer necessary.

### Durability and robustness

- ▶ The use of high-tech material and long life components, enhance the machine's uptime, while reducing service and repair costs to a minimum.

### Simple to use and easy maintenance

- ▶ All components needing frequent maintenance are color-coded in yellow and can be removed easily without tools. The dashboard is self-explanatory and displays all relevant information. These features allow trouble-free operation and require minimum operator training.
-

# TASKI swingo 755 B Specifications

## Technical Data

| Description                                    |                               | Description                                     |                  |
|--|-------------------------------|---|------------------|
| Theoretical performance (Economy / Power)      | 1290 / 1935 m <sup>2</sup> /h | Dimensions (L x W x H)                          | 116x47.5x119.5cm |
| Working width                                  | 43 cm                         | Turning circle                                  | 1.12 m           |
| Squeegee width                                 | 69 cm                         | Brush system                                    | 1 x 43 cm        |
| Solution tank (nominal)                        | 40 l                          | Brush pressure (with / without wheel drive)     | 40/43 kg         |
| Recovery tank (nominal)                        | 40 l                          | Working speed (power)                           | 3.0 /4.5 km/h    |
| Nominal consumption                            | 900 W                         | Power cord length of integrated battery charger | 3 m              |
| Rated voltage                                  | 24 V                          | Sound level                                     | 58 dB(A)         |
| Battery capacity                               | 50-70 Ah/C5                   | Electrical protection class (BMS/non-BMS)       | I/III            |
| Battery run time (nominal)                     | 2 h                           | Approvals                                       | CE/CB Test cert. |
| Machine weight ready for use (Economy / Power) | 155/160 kg                    |   |                  |

## TASKI swingo 755 B

| Model                          | SKU Number |
|--------------------------------|------------|
| TASKI swingo 755 B Economy     |            |
| TASKI swingo 755 B Economy BMS |            |
| TASKI swingo 755 B Power       |            |
| TASKI swingo 755 B Power BMS   |            |

## Accessories/Additional Parts

| Description                                | SKU Number                       |
|--|----------------------------------|
| Pad drive harpoon grip 43 cm               | 7510829                          |
| Scrubbing brush standard 43cm              | 8504750                          |
| Scrubbing brush washed concrete 43cm       | 8504800                          |
| Scrubbing brush abrasive 43 cm             | 8504780                          |
| Filling hose with universal water coupling | 8502830                          |
| TASKI JFit kit for swingo 755/855/1255     | 7517125                          |
| Variety of polyester and contact pads      | Please refer to local price list |

## Additional Features

**BMS (Battery Management System):** Integrated in the machine, the battery charger prevents deep discharging of the battery and monitors the charging process.

**WD (Wheel Drive):** The variable working speed up to 4.5 km/h and reverse speed up to 3 km/h guarantees ergonomic and effortless utilization and increases performance compared to non-wheel drive models.

**CSD (Cleaning Solution Dosing):** The CSD system allows for a speed-dependent supply of cleaning solution. This feature ensures that the amount of solution dosed onto the floor is always constant—no matter how fast the machine is operating. The result? No puddles in curves and turns as well as a 30-50 % saving in cleaning solution, leading to significantly increased productivity of the machine.